

**CHORE-TIME**®




The Chore-Time TURBO-COOL™ Evaporative Cooling System's one-piece trough is easy to install – no joints to glue and dry and no holes to be cut.

## TURBO-COOL™ EVAPORATIVE COOLING SYSTEM

MANUFACTURED USING HIGH-QUALITY REINFORCED MATERIALS FOR LONG LASTING DURABILITY

- › Improve conditions for increased animal productivity and comfort
- › Easy to install and clean
- › Easy to see water jets and check water pressure



# TURBO-COOL™ EVAPORATIVE COOLING SYSTEM

**Manufactured using high-quality reinforced materials for long lasting durability.**

## Open Top Design

- > Unique, large 2-inch (51-mm) pipe and 5/32-inch (4-mm) water distribution holes.
- > Easy to see water jets and check water pressure.
- > Easy access to pipe for cleaning.
- > Pipe includes removable end plugs for cleaning.
- > Includes rubber water-containment seals at system ends.

## Reinforced, Continuous, One-Piece Trough

- > One-piece trough is made of heavy-duty, ultraviolet-resistant polypropylene with no problematic joints where leaks and breaks tend to occur in others' systems.
- > Fabric-reinforced trough material is proven under the harshest conditions and provides self-contained water storage.
- > Unlike competitors' rigid plastic troughs, the Chore-Time seamless trough design is easy to install, saving time and expense on new construction or retrofit projects.
- > Uniform water distribution from one end up to 75 feet (22.8 m), or 110 feet (33.5 m) with a center-mounted sump.



## High-Performance 6-Inch (152-mm) Cooling Pad

- > Standard 45/15 fluting and 12-inch (305-mm) pad width.
- > Pad heights: 2, 3, 4, 5 or 6 feet (610, 914, 1219, 1524 or 1829 mm).
- > Standard pad includes black protective coating. Protective bottom coating is optional.



Well-designed, innovative sump tank holds heavy-duty, submersible pump. Includes reinforcing ribs, a drain plug, automatic float valve, low-water safety switch, bleed-off valve and easy-access shut off.

90-Degree Around-the-Corner Kit is available for wider house applications. Sump pump must be installed on the side with the longest pad length.



Designed for easy pad removal for cleaning without hardware or tools. Full-width plastic tray improves support and extends pad life.



Use the pulsing option of Chore-Time's CHORE-TRONICS® Control to wet just part of the pad for more precise control of cooling. Reduce rapid temperature fluctuations.

